



A1. Model No.: A2. Product Name: SV-AC552 Automotive Mobile Power Battery **B1. Product Features:** 1. Fast charge 2. Wide input voltage DC 5~24V 3. Switch on/off button 4. Low standby power consumption 5. Charging capacity indicator light 6. Discharging capacity indicator light 7. Overcharge protection 8. Overdischarge protection 9. Overload/short circuit protection 10. Over temperature protection 11. Load detection Power Adapter Optional for Charging 12. Magnetic base mount 13. UPS (Uninterrupted Power Supply) **B2. Key Specifications:** 1. Battery Capacity: 9600mAh/3.6V TIPS DC 5~24V 2. Charging Voltage: 1. To protect the battery from damage, please charge it 3.3H(DC 12/24V at 25°C) 7H(DC 5V at 3. Charging Time: to 75% of capacity before storing it for a long period of 25℃) time, and charge it again to 75% within 150 days. 4. Discharging Voltage: 9.5~12.6V(10.8V) 2. After being stored for long time, the initial charging 5. Discharging Time 17.5H (160mA~180mA/12V) current might be relatively low, but will get back to 6. Charging Temperature: -10 ~ 45℃ normal after a while. 7. Discharging Temperature: -20 ~ 60℃ 3. AC Adapter (charger) is recommended for charging. -20 ~ 60℃ 8. Storage Temperature: 9. Waterproof Rating: IP69K 10. Dimension: 100.5*64.5*40.7 (mm) C1. Accessories: 1- Manual 1-DC male-USB male D1. Packing: Weight Of Unit Product: Weight Of Export Carton: 400g Dimension Of Giftbox: 12.2*8.6*9.2cm Dimension Of Export Carton: 20"/40"/40"HQ Qtv: Qtv Per Carton: F1. Warranty Term: E1. Payment Terms: T/T 18 months of warranty G1. Certificates: H1. Rerence Price & Lead time: Sample: USD 53.00 Lead time: G-Sensor Optional +USD 12.50 Adapter USD 4.95 Optional: I1. Remarks: