





## **Technical Specifications**

Resolution	1024 x 600
Screen Size	7" diagonal
Dot Pitch	0.516 (H) x 0.1432 (V)
View options	Single, split, triple, quad
Brightness	500 cd/m2
Contrast ratio	800:1
Viewing Angle	U/D: 70° L/R: 75°
Aspect Ratio	16:9
Video Inputs	4
Audio Inputs	4
Input Triggers	1
Trigger Priorites	5
Input Voltage	DC 10 - 32V
Power Consumption	max 25W
Operating Temp	-20°~70°C
Storage Temp	-30°~80°C
Dimension	195 x 130 x 47mm
Weight	1KG
Waterprrof rating	IP66

Proudly Designed and Developed in Australia



## **Proxicam LCD**

Full-Colour HD Monitor with Proximity Alerts

SKU: PX-LCD

## **Key Features**

- Enhances visibility with up to 4 Proxicam smart cameras for 360° all-around views and pedestrian awareness.
- Spoken voice notification and a choice of audible warnings, across a range of pitch, provide operator alerts in all types of noisy environments.
- On-screen visual notification of detection and proximity breach events.
- Bright 7" TFT LCD display, with auto dimming, viewable in all light conditions.
- Touch-screen interface with easy-to-use menu.
- Anti-tamper screen lock with 8 character alpha-numeric password protection.
- Quick setup function allows for commonly-used configurations.
- **Input trigger f**or reverse or auxillary activation.
- Water and dust proof IP66 rating to withstand harsh working environments.
- Supplied with stainless steel U-bracket.
- (Optional) T-slot ball joint brackets for mounting to posts and bars.



